



EZRV SOLUTIONS

RV SNAP TRAP[®]

INSTALLATION INSTRUCTIONS



SP54-267



Above. Beyond. Always.

RV SNAP TRAP®

INSTALLATION INSTRUCTIONS

INTRODUCTION

Revolutionize your RV experience with the RV Snap Trap®, the industry's first and only snap-on P-trap for RV sewer hoses. Designed for convenience, versatility, and peace of mind, the RV Snap Trap™ is a must-have for hassle-free campsite living and extended gray tank valve usage.

IMPORTANT: The RV Snap Trap® requires the use of a standard hose support.

INSTALLATION

STEP 1

Pull the minimum amount necessary of the sewer hose support to make room for the trap.

STEP 2

The trap may be installed at any point within the sewer hose support run to best suit the conditions and terrain of the campsite. The middle of the hose support run is the most common.

STEP 2

Under normal use, allow the holding tank to fill to approximately two-thirds full.

STEP 3

Allow the cleaning solution to work in the holding tank for a minimum of 24 hours.

STEP 4

Once the holding tank reaches two-thirds full or greater, open the gate valve and drain the tank completely.

TANK CLEAN-OUT

A quarterly clean-out (every 3 months) is recommended for grey holding tanks that have been left in the open valve condition and in continual use for extended periods of time.

STEP 1

Close the gate valve and pour approximately 2 ounces of Dawn Ultra® dish soap into any drain connected to the holding tank to be cleaned.



Above. Beyond. Always.